



AK258



SIZE: 254X89mm

LIFE: 50000Hrs/40°C

| Model No. | Rated VAC | Freq. Hz | Rated Input Current | Rated Input Watt | Rated Speed RPM | Max. Air Flow | | Max. Static Pressure | | Noise Level dB(A) |
|-----------|-----------|-------------|---------------------|------------------|--------------------|---------------------|---------|----------------------|-----------------------|----------------------|
| | V | | A | W | | M ³ /MIN | CFM | mm-H ₂ O | inch-H ₂ O | |
| AK2581HB | 100 | 50/60 | 0.55/0.62 | 60/67 | 2150/2000 | 24.5/22.8 | 867/806 | 11.7/9.4 | 0.46/0.37 | 56±2 |
| AK2581MB | 115 | | 0.22/0.24 | 34/37 | 1400/1600 | 17.0/18.8 | 600/665 | 6.9/9.1 | 0.27/0.36 | 51±2 |
| AK2582HB | 200 | 50/60 | 0.26/0.30 | 60/67 | 2300/2200 | 25.9/25.1 | 915/886 | 12.4/10.4 | 0.49/0.41 | 58±2 |
| AK2582MB | 220 | | 0.16/0.14 | 34/37 | 1400/1600 | 17.0/18.8 | 600/665 | 6.9/9.1 | 0.27/0.36 | 51±2 |

