


UNIT:mm



Model (型号)	Part Number Terminal Leadwire (端子/引线)	Bearing System (轴承)	Rated Voltage (V) (电压)	Freq. (Hz) (频率)	Current (A) (电流)	Input Power (W) (功率)	Speed (RPM) (转速)	Air Flow (CFM) (风量)	Static Pressure (Inch-H <sub>2</sub> O) (静压) (静压)	Noise Level (dB-A) (噪音值) (噪音值)	Weight (g) (重量)
SJ1238HA1	1238HA1SAT(L) 1238HA1BAT(L)	Sleeve Ball	110/120	50/60	0.210/0.28	18/25	2600/3000	84/90	0.28/0.34	45/51	520
SJ1238HA2	1238HA2SAT(L) 1238HA2BAT(L)	Sleeve Ball	220/240	50/60	0.090/0.12	15/22	2600/3000	84/90	0.28/0.34	45/51	520
SJ1238MA1	1238MA1SAT(L) 1238MA1BAT(L)	Sleeve Ball	110/120	50/60	0.130/0.17	18/14	2500/2800	80/90	0.18/0.24	38/43	520
SJ1238MA2	1238MA2SAT(L) 1238MA2BAT(L)	Sleeve Ball	220/240	50/60	0.070/0.09	11/16	2500/2800	80/90	0.18/0.24	38/43	520
SJ1238LA1	1238LA1SAT(L) 1238LA1BAT(L)	Sleeve Ball	110/120	50/60	0.130/0.12	9/11	1900/2500	65/78	0.10/0.18	35/40	520
SJ1238LA2	1238LA2SAT(L) 1238LA2BAT(L)	Sleeve Ball	220/240	50/60	0.050/0.06	9/11	1900/2500	65/78	0.10/0.18	35/40	520